



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	ATTORNEY DOCKET NO. CONFIRMATION NO.	
09/487,529	01/19/2000	David A. Wood	5181-38400 3267		
7590 06/29/2005			EXAMINER		
B. NOEL KIVLIN			HOANG, PHUONG N		
MEYERTONS, HOOD, KIVLIN, KOWERT & GOETZEL, P.C. P.O. BOX 398 AUSTIN, TX 78767-0398			ART UNIT	PAPER NUMBER	
			2194		

DATE MAILED: 06/29/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)			
Office Action Summary	09/487,529	WOOD ET AL.			
Smoo Addon Gammary	Examiner N. Hoons	Art Unit			
The MAILING DATE of this communication ap	Phuong N. Hoang pears on the cover sheet with the	2194 correspondence address			
Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.  - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.  - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).					
Status					
1) Responsive to communication(s) filed on 20 December 2004.					
2a) ☐ This action is <b>FINAL</b> . 2b) ☑ This action is non-final.					
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims					
4)⊠ Claim(s) <u>1 - 30</u> is/are pending in the application.					
4a) Of the above claim(s) is/are withdrawn from consideration.					
5) Claim(s) is/are allowed.					
6) Claim(s) 1 - 30 is/are rejected.					
7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or election requirement.					
Application Papers					
9) The specification is objected to by the Examiner.					
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.  Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).					
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).					
11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.					
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).					
a) All b) Some * c) None of:					
1. Certified copies of the priority documen	ts have been received.				
2. Certified copies of the priority documen	ts have been received in Applica	tion No			
3. Copies of the certified copies of the priority documents have been received in this National Stage					
application from the International Bureau (PCT Rule 17.2(a)).  * See the attached detailed Office action for a list of the certified copies not received.					
See the attached detailed Office action for a list	tor the certified copies hot receiv	ST. JOHN COURTENAY III			
Attachment(s)	<b>4.□ 4. • •</b>	PRIMARY FYAMINGS			
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Linterview Summar Paper No(s)/Mail D	y (P10-413) Date			
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08 Paper No(s)/Mail Date	5) Notice of Informal 6) Other:	Patent Application (PTO-152)			
U.S. Patent and Trademark Office	· — — — — — — — — — — — — — — — — — — —				
	ction Summary P	art of Paper No./Mail Date 20050622			

Art Unit: 2194

### **DETAILED ACTION**

1. Claims 1 – 30 are pending for examination.

## Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-7, 15-16, 18-21, 23, and 27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chih-Lui I, US patent no. 6,088,335 in view of Shad, US patent no. 5,410,536.
- 4. Chih-Lui I reference was cited in the last office action.
- 5. **As to claim 1**, Chih-Lui I teaches a computer system comprising the steps of: a first device (mobile station, col. 7 lines 35 45); and a second device (base station, col. 7 lines 35 60) coupled to the first device:

wherein the first device is configured to convey a first request (mobile station signals a request to the base station, col. 7 lines 35 - 60) to the second device, wherein the second device is configured to receive the first request, wherein the second device is configured to detect a temporarily unavailable condition (if the scheduled list is longer than the threshold L, the mobile is told to retry later (retry delay) in step 415. The base station selects the value of this parameter based upon loading conditions at that base station, col. 8 lines 20 - 30), wherein the second device is configured to convey a response to the first device corresponding to the first request, and wherein the response includes a delay value (retry delay, col. 8 lines 20 - 30) corresponding to the temporarily unavailable condition.

Chih-Lui I does not explicitly teach the step of the first device and the second device are configured to cause an error recovery mechanism to be initiated in response to detecting that a retry limit corresponding to the first request is exceeded.

Shah teaches the step of the first device and the second device are configured to cause an error recovery (both nodes are always involved in error recovery......"Regry limit exceeded", col. 19 lines 50 – 63) mechanism to be initiated in response to detecting that a retry limit corresponding to the first request is exceeded.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chih-Lui I and Shah's system because Shah's error recovery when retry limit exceeded would enable both devices always recognize an error while performing a retry option and remain synchronized.

Art Unit: 2194

6. **As to claim 2**, Chih-Lui I teaches the step of the first device is configured to receive the response (the mobile receives a delay parameter in a data burst assignment message, , col. 8 lines 20 - 60), and wherein the first device is configured to convey a second request (it initiates such a delay, before starting its transmission of the assigned burst length, col. 8 lines 20 - 60) to the second device at a time corresponding to the delay value.

- 7. **As to claim 3**, Chih-Lui I teaches the step of in response to receiving the first request the second device is configured to generate delay value according to a type of the temporarily unavailable condition (based upon loading conditions, col. 8 lines 20 30) detected at the second device (at the base station).
- 8. **As to claim 4**, Chih-Lui I teaches the step of wherein the delay value corresponds to a first value (basic rate, col. 9 lines 45 col. 10 lines 24) in response to the temporarily unavailable condition corresponding to a first type of condition and wherein the delay value corresponds to a second value (high rate, col. 9 lines 45 col. 10 lines 24) in response to the temporarily unavailable condition corresponding to a second type of condition.
- As to claim 5, Chih-Lui I teaches the step of wherein the second device is configured to calculate delay value using one or more variables (m, a1, col. 10 and col. 13) that correspond to one or more previous temporarily unavailable conditions.

Art Unit: 2194

10. **As to claim 6,** Chih-Lui I teaches the step of wherein the delay value corresponds to an encoded value (col. 10 and 13).

- 11. **As to claim 7**, Shad teaches wherein one of different types of error recovery mechanism is to be initiated based on a type of temporarily unavailable condition at the second device (error recover actions are based on the type of error, col. 3 lines 3 20).
- 12. **As to claim 15,** it is a method claim of claim 1. See rejection for claim 1 above.
- 13. **As to claim 16**, see rejection for claim 2 above.
- 14. **As to claim 18**, see rejection for claim 6 above.
- 15. **As to claim 19**, Chih-Lui I teaches the steps of determining a type of the temporarily unavailable condition (loading conditions, col. 8 lines 20 30); and generating the delay value (retry delay, col. 8 lines 20 30) according to the type of the temporarily unavailable condition.
- 16. **As to claim 20,** see rejection for claim 5 above.
- 17. **As to claim 21**, see claim 7 above.

Application/Control Number: 09/487,529

Page 6

Art Unit: 2194

18. As to claim 23, see rejection for claim 5 above.

- 19. **As to claim 27**, Chih-Lui I teaches the step of the wherein said first device is configured to receive said response including the delay value, wherein said first device is configured to convey a second request to said second device at a time corresponding to the delay value (col. 8 lines 15 30), and wherein if the second device detects a temporarily unavailable condition when the second request is received at the second device, the second device is configured to determine a second delay value based on the temporarily unavailable condition detected at the second device (col. 8 lines 15 30 and col. 11 lines 45 50).
- 20. Claims 8 9, 12 13, and 30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chih-Lui I, US patent no. 6,088,335 in view of Bailey, US patent no. 5,189,734.
- 21. **As to claim 8,** Chih-Lui I teaches a computer system comprising the steps of: a first device (mobile station, col. 7 lines 35 45); and a second device (base station, col. 7 lines 35 60) coupled to the first device; wherein the first device is configured to convey a first request (mobile station signals a request to the base station, col. 7 lines 35 60) to the second device,

wherein the second device is configured to receive the first request, wherein the second device is configured to detect a temporarily unavailable condition (if the scheduled list is longer than the threshold L, the mobile is told to retry later (retry delay) in step 415. The base station selects the value of this parameter based upon loading conditions at that base station, col. 8 lines 20 - 30), wherein the second device is configured to convey a response to the first device corresponding to the first request, and wherein the response includes a delay value (retry delay, col. 8 lines 20 - 30) corresponding to the temporarily unavailable condition.

Chih-Lui I does not explicitly teach the step of wherein the second device is configured to store historical data corresponding to previous temporarily unavailable conditions, wherein the second device is configured to determine the delay value based on the stored historical data.

Bailey teaches the step of the second device is configured to store historical data corresponding to previous temporarily unavailable conditions (base station maintain information about loss of service due to adjacent cells being full, cells which are temporarily out of use due to fault in a base station, or there are no adjacent cells in the estimated direction of travel, col. 6 lines 1-25), wherein the second device is configured to determine the delay (delay) value based on the stored historical data.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chih-Lui I and Bailey's system because Bailey's error log would provide information to determine the delay and can be reused later when the same error repeats.

Art Unit: 2194

22. **As to claim 9**, Chih-Lui I teaches the step of wherein the communications medium comprises a switching network (central switch, col. 4 lines 1 - 4).

- 23. **As to claim 12**, Chih-Lui I teaches the step of in response to receiving the first request the second device is configured to generate delay value according to a type of the temporarily unavailable condition (based upon loading conditions, col. 8 lines 20 30) detected at the second device (at the base station).
- 24. **As to claim 13,** Chih-Lui I does not explicitly teach the step of wherein the delay value corresponds to an encoded value (col. 10 and 13).
- 25. **As to claim 30**, Chih-Lui I teaches a computer system comprising the steps of: a first device (mobile station, col. 7 lines 35 45); and

a second device (base station, col. 7 lines 35 - 60) coupled to the first device; wherein the first device is configured to convey a first request (mobile station signals a request to the base station, col. 7 lines 35 - 60) to the second device, a delay value (retry delay, col. 8 lines 20 - 30) corresponding to the temporarily unavailable condition, and delay value is a programmable value (col. 8 lines 15 – 30 and col. 11 lines 45 - 50).

Chih-Lui I does not explicitly teaches the step of a delay value is associated with each of the plurality of temporarily unavailable condition.

Bailey teaches the step of the second device can detect the plurality of temporarily unavailable condition (base station maintain information about loss of service due to adjacent cells being full, cells which are temporarily out of use due to fault in a base station, or there are no adjacent cells in the estimated direction of travel, col. 6 lines 1 - 25).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chi-Lui I and Bailey's system because Bailey's detecting a plurality of temporarily unavailable conditions would provide a variety of detected errors for the second device and once the type of errors has been detected, the second device can generate the delay value that is associated with each of the error.

- 26. Claims 10 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chih-Lui I, US patent no. 6,088,335 in view of Bailey, US patent no. 5,189,734, and further in view of Chambers, US patent no. 5,884,052.
- 27. As to claim 10, Chih-Lui I and Bailey do not teach the step of wherein the communications medium comprises a shared bus.

Art Unit: 2194

Chamber teaches the step of wherein the communications medium comprises a shared bus (PCI bus, col. 6 - 8).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chih-Lui I, Bailey, and Chamber's system because Chamber's shared bus would be necessary to provide the communication on the network.

- 28. **As to claim 11**, Chamber teaches the computer system of claim 8, wherein the communications medium comprises an arbitrated loop (the PCI agent attempts a subsequent access.....arbitrates for and acquires ownership of the PCI bus, col. 8 lines 40 50).
- 29. Claims 14 is rejected under 35 U.S.C. 103(a) as being unpatentable over Chih-Lui I, US patent no. 6,088,335 in view of Bailey, US patent no. 5,189,734, and in view of Shad, US patent no. 5,410,536.
- 30. **As to claim 14**, Chih-Lui I and Bailey do not teach the step of the first device and the second device are configured to cause an error recovery mechanism to be initiated in response to detecting that a retry limit corresponding to the first request is exceeded.

Shah teaches the step of the first device and the second device are configured to cause an error recovery (both nodes are always involved in error recovery......"Regry

limit exceeded", col. 19 lines 50 – 63) mechanism to be initiated in response to detecting that a retry limit corresponding to the first request is exceeded. It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chih-Lui I, Bauiley, and Shah's system because Shah's error recovery when retry limit exceeded would enable both devices always recognize an error while performing a retry option and remain synchronized.

- 31. Claims 17, 22, 24 26 and 28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chih-Lui I, US patent no. 6,088,335 in view of Shad, US patent no. 5,410,536, and further in view of Bailey, US patent no. 5,189,734.
- 32. **As to claim 17**, Chih-Lui I and Shad do not teach the step of the second device is configured to store historical data corresponding to previous temporarily unavailable conditions, wherein the second device is configured to determine the delay value based on the stored historical data.

Bailey teaches the step of the second device is configured to store historical data corresponding to previous temporarily unavailable conditions (base station maintain information about loss of service due to adjacent cells being full, cells which are temporarily out of use due to fault in a base station, or there are no adjacent cells in the estimated direction of travel, col. 6 lines 1-25), wherein the second device is configured to determine the delay (delay) value based on the stored historical data.

Art Unit: 2194

It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chih-Lui I, Shad, and Bailey's system because Bailey's error log would provide information to determine the delay and can be reused later when the same error repeats.

- 33. **As to claim 22,** Chih-Lui I teaches the second device generate delay value (retry delay, col. 8 lines 15 30) based on a number of response corresponding to the temporarily unavailable condition (Bailey, col. 6 lines 1- 25).
- 34. **As to claim 24**, see rejection for claim 17 above.
- 35. **As to claims 25 and 26**, Chih-Lui I teaches the step of the delay value may be generated according to a static and dynamic algorithm based on the previous (select value based on loading condition, col. 8 lines 15 30).
- 36. **As to claim 28**, Bailey teaches the step of wherein said type of said temporarily unavailable condition is a temporarily loss of system resources, a temporary lack of processing resources on the second device (there are no adjacent cells in the estimated direction of travel, col. 6 lines 1-25), or a lack of a valid virtual to physical address translation.

Art Unit: 2194

37. Claim 29 is rejected under 35 U.S.C. 103(a) as being unpatentable over Chih-Lui I, US patent no. 6,088,335 in view of Shad, US patent no. 5,410,536, and further in view of Barlow, US patent no. 5,210,867.

38. **As to claim 29**, Chih-Lui I and Shah do not explicitly teach the step of wherein said first device is configured to ignore said delay value received from the second device and independently determine when to send a second request.

Barlow teaches the step of ignore said delay value received from the second device and independently determine when to send a second request (ignore the NAK response and wait for a slow NAKR, col. 8 lines 55 – col. 9 lines 2).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Chih-Liu I, Shad, and Barlow's system because Barlow's decision when to resend the request would provide an option and the flexibility for the first device to determine when to resend the request that is suitable with demand or the convenience of the device.

## Response to Arguments

39. Applicant's arguments filed 12/20/04 have been considered but are moot in view of the new ground(s) of rejection.

Art Unit: 2194

### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Phuong N. Hoang whose telephone number is (571)272-3763. The examiner can normally be reached on Monday - Friday 9:00 am to 5:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Meng-Ai An can be reached on (571)272-3756. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Ph June 25, 2005

ST. JOHN COURTENAY IN PRIMARY EXAMINER